



Your chimney for life

DECLARATION OF PERFORMANCE

DOP 109055214 - DUALINOX WG (25mm Insulation)

1. Unique identification code of the product-type:

DUALINOX WG

Double wall chimney system according to EN 1856-1 : 2009

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11 (4):

Diameter	EN 1856-1 : 2009 (8.1)
Ø 80 => 300	T200 P1 W Vm L20040 O20 T250 N1 D Vm L20040 O20 T450 N1 D Vm L20040 G75
Ø 350 => 400	T200 P1 W Vm L20040 O30 T250 N1 D Vm L20040 O30 T450 N1 D Vm L20040 G115
Ø 450	T200 P1 W Vm L20050 O30 T250 N1 D Vm L20050 O30 T450 N1 D Vm L20050 G115
Ø 500 => 600	T200 P1 W Vm L20050 O40 T250 N1 D Vm L20050 O40 T450 N1 D Vm L20050 G150
Ø 650 => 750	T200 P1 W Vm L20080 O80 T250 N1 D Vm L20080 O80 T450 N1 D Vm L20080 G300

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Convey the products of combustion from heating appliances to the outside atmosphere

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

POUJOLAT Sp. z o.o. - ul. Olszankowa 45 - 05-120 Legionowo - POLAND

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 2+ and system 4

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

Notified factory production control certification body N° 0071 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity 0071-CPR-0038 of the factory production control.


8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not applicable

9. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
9.1 Compressive strength	Ø80 -> Ø750: 16m	EN 1856-1 : 2009
9.2 Resistance to fire	Ø80 -> Ø300: T200 & T250 O20 Ø80 -> Ø300: T450 G75 Ø350 -> Ø450: T200 & T250 O30 Ø350 -> Ø450: T450 G115 Ø500 -> Ø600: T200 & T250 O40 Ø500 -> Ø600: T450 G150 Ø650 -> Ø750: T200 & T250 O80 Ø650 -> Ø750: T450 G300	
9.3 Gas tightness / leakage	N1 (<2 l/s.m² - 40 Pa) P1 (<0,006 l/s.m² - 200 Pa)	
9.4 Flow resistance of chimney sections fittings and terminals	In accordance to norm	
9.5 Thermal resistance	0,33 m².K/W - 200°C	
9.6 Sootfire resistance	O: T200 & T250: - No G: T450: - Yes	
9.7 Thermal performance under normal operating conditions	Ø80 -> Ø750: T200 & T250 & T450	
9.8 Flexural tensile strength	Ø80 -> Ø750: 3m	
9.9 Non vertical installation	In accordance to norm	
9.10 Condensate penetration resistance	Ø80 -> Ø750: T200: W Ø80 -> Ø750: T250 & T450: D	
9.11 Durability against corrosion	Ø80 -> Ø400: 0,4 mm Ø450 -> Ø600: 0,5 mm Ø650 -> Ø750: 0,8 mm Vm (1.4301)	
9.12 Components subject to wind load	Ø80 -> Ø750: 3m	
9.13 Compressive strength	Ø80 -> Ø750: 16m	
9.14 Freeze thaw resistance	Passed	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.



Signed for and on behalf of the manufacturer by:
Tomasz RAWIAK, Operational Director
Legionowo, 2018/08/14