



## DECLARATION OF PERFORMANCE

DOP 051032713GB

1. Unique identification code of the product-type:

**TUBAGINOX GF-P**  
*Metal flue liners - EN 1856-2 : 2009*

2. Type, batch or serial number or any other element allowing identification of the construction product:

<b>EN 1856-2 : 2009 (8.2)</b>
T120 P1 W Vm L50010 O T600 P1 W Vm L50010 O

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

*Convey the products of combustion from appliances to the outside atmosphere*

4. Name, registered trade name or registered trade mark and contact address of the manufacturer:

*POUJOLAT SA - CS 50016 - 79270 SAINT-SYMPHORIEN, France*

5. Name, registered trade name or registered trade mark and contact address of the distributor:

6. System or systems of assessment and verification of constancy of performance of the construction product:

*System 2+: Metal flue liners, connecting flue pipes and fittings and System 4: Terminals*

7. The declaration of performance concerning a construction product is covered by a harmonised standard:  
Laboratoire National de métrologie et d'Essais (n°0071)

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.  
Signed for and on behalf of the manufacturer by: *Erwan CRENN, Factory Director*

Saint Symphorien, 10/13/2020

## 8.2 - Declared performance in compliance with EN 1856-2 : 2009 use as metal flue liners

Essential characteristics	Performance	Harmonised technical specification
Installed length	Ø 80, 100, 125, 130, 140, 150, 155, 167, 180, 200, 230, 250, 300	EN 1856-2 : 2009
Gas tightness / Leakage	Pass to P1 with seal (<0,006 l/s.m <sup>2</sup> - 200 Pa)	
Sootfire resistance	T120 O T600 O	
Mechanical resistance	See installation instructions	
Flow resistance	r = 0,005 m	
Condensate penetration resistance	W	
Corrosion resistance	0,10 mm Vm (1.4404)	
Freeze thaw resistance	Pass	